

THOMSON

DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

## The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent](#) [Email this to a](#)

? Title: **JP59131638A2: OPEN-CELL FOAMED MATERIAL OF CROSSLINKED POLYOLEFIN HAVING HYDROPHILIC PROPERTY AND ITS PREPARATION**

? Derwent Title: Crosslinked polyolefin open-cell foam - prepd. from polyolefin, foaming agent and crosslinking agent [\[Derwent Record\]](#)

? Country: **JP** Japan  
? Kind: **A**

? Inventor: **YOSHIDA IWAO;  
KAWASHIMA YASUO;  
KASATSUGU TAKEO;**

? Assignee: **SANWA KAKO KK**  
[News, Profiles, Stocks and More about this company](#)

? Published / Filed: **1984-07-28 / 1983-01-18**

? Application Number: **JP1983000006899**

? IPC Code: **C08J 9/06; C08J 9/22;**

? Priority Number: **1983-01-18 JP1983000836899**

? Abstract: **PURPOSE:** To obtain a foamed material having excellent hydrophilic property, water retainability and weather resistance, and the feeling of the human skin, by kneading a polyolefin with a foaming agent and a crosslinking agent, heating the kneaded product under normal pressure to obtain a foamed material, interconnecting the cells of the material by mechanical deformation, and impregnating a water-insolubilized polyvinyl alcohol to the foam.

**CONSTITUTION:** A foamable and crosslinkable kneaded composition composed of a polyolefin, a foaming agent and a crosslinking agent and free of gel fraction, is heated under normal pressure to effect the simultaneous decomposition of the foaming agent and the crosslinking agent to obtain a foamed material, which is subjected to the mechanical deformation to interconnect the cells with each other. An open-cell foamed material having uniform and fine cell structure and elasticity, an expansion ratio of 15W70 and an open-cell ratio of  $\square 80\%$  can be manufactured by this process. A water-insolubilized polyvinyl alcohol is impregnated in the pore. The polyvinyl alcohol has a polymerization degree of about 500W2,000, and the amount is 0.001W0.02g per 1cm<sup>3</sup> of the foamed material.

**COPYRIGHT:** (C)1984,JPO&Japio

? Family: None

? Other Abstract None

